According to 1907/2006 EEC Article 31

Page 1/8

Printing date: 13.03.2017 Version: 40 Revision: 13.03.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Zettex High Wax Polish
- · Article number:
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use
- SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- SU21 Consumer uses: Private households / general public / consumers
- · Product category
- PC31 Polishes and wax blends
- PC35 Washing and cleaning products (including solvent based products)
- · Process category
- PROC7 Industrial spraying
- PROC11 Non industrial spraying
- · Application of the substance / the mixture Exterior vehicle cleaner
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Zettex Europe BV

Plaza 20, 4782 SK Moerdijk

The Netherlands

+31(0)888-938839

info@zettex.nl

www.zettex.nl

• **1.4 Emergency telephone number:** +31(0)888-938839

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- · Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P251 Do not pierce or burn, even after use.
- P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

(Contd. on page 2)

(Contd. of page 1)

Safety data sheet According to 1907/2006 EEC Article 31

Printing date: 13.03.2017 Version: 40 Revision: 13.03.2017

Trade name: Zettex High Wax Polish

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Active substance with propellant

· Dangerous components:		
CAS: 106-97-8	butane (containing < 0.1% butadiene (203-450-8))	10-<25%
EINECS: 203-448-7	Flam. Gas 1, H220; Press. Gas C, H280	
Reg.nr.: 01-2119474691-32		
CAS: 74-98-6	propane	2.5-<10%
EINECS: 200-827-9	Flam. Gas 1, H220; Press. Gas C, H280	
Reg.nr.: 01-2119486944-21		

_

· Ingredients according to detergents guidline 648/2004/EC		
aliphatic hydrocarbons	≥15 - <30%	
non-ionic surfactants, perfumes (AMYL CINNAMAL, AMYL CINNAMAL), METHYLISOTHIAZOLINONE	<5%	

· Additional information:

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- \cdot 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

Printing date: 13.03.2017 Version: 40 Revision: 13.03.2017

Trade name: Zettex High Wax Polish

(Contd. of page 2)

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

\cdot Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

 $\cdot \textbf{Additional information about design of technical facilities:} \ No \ further \ data; see item \ 7.$

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane (containing < 0.1% butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

74-98-6 propane

OEL Short-term value: 3600 mg/m³, 2000 ppm Long-term value: 1800 mg/m³, 1000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

(Contd. on page 4)

Printing date: 13.03.2017 Version: 40 Revision: 13.03.2017

Trade name: Zettex High Wax Polish

(Contd. of page 3)

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.5 \text{ mm}$

· Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses



Tightly sealed goggles

· **Body protection:** Use protective suit. (EN-13034/6)

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Aerosol

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

• **pH-value:** Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

(Contd. on page 5)

Printing date: 13.03.2017 Version: 40 Revision: 13.03.2017

Trade name: Zettex High Wax Polish

	(Contd. of page
Initial boiling point and boiling range	e: -0.5 °C
· Flash point:	-97 °C
· Flammability (solid, gas):	Not applicable.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.7 Vol %
Upper:	10.9 Vol %
· Vapour pressure at 20 °C:	2100 hPa
· Density at 20 °C:	0.85 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	28.5 %
Water:	67.7 %
Solids content:	1.6 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
Hydrocar	Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%		
Oral	LD50	>5000 mg/kg (rat)	
Dermal	LD50	>5000 mg/kg (rabbit)	
Inhalative	LC50/4h	>4951 mg/l (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date: 13.03.2017 Version: 40 Revision: 13.03.2017

Trade name: Zettex High Wax Polish

(Contd. of page 5)

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

	· Aquatic toxicity:		
Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%			
	EL0 (48h)	1000 mg/l (Daphnia magna)	
	EL0(72h)	1000 mg/l (Pseudokirchneriella subcapitata)	
	LL0(96h)	1000 mg/l (Oncorhynchus mykiss (96h))	

- · 12.2 Persistence and degradability Easily biodegradable
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · **Recommendation:** Disposal must be made according to official regulations.

14.1 UN-Number ADR, ADN, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR, ADN	UN1950 AEROSOLS	
· IMDG	AEROSOLS	
· IATA	AEROSOLS, flammable	

(Contd. on page 7)

Printing date: 13.03.2017 Version: 40 Revision: 13.03.2017

Trade name: Zettex High Wax Polish

	(Contd. of pag
14.3 Transport hazard class(es)	
ADR	
**	
Class	2 5F Gases.
Label	2.1
ADN	
ADN/R Class:	2 5F
IMDG, IATA	
~	
Class	2.1
Label	2.1
14.4 Packing group	W. 1
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above
	1 litre: Category B. For WASTE AEROSOLS: Category
	C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1
	litre: Segregation as for class 9. Stow "separated from"
	class 1 except for division 1.4. For AEROSOLS with a
	capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
1477	
14.7 Transport in bulk according to Anne Marpol and the IBC Code	X II of Not applicable.
Transport/Additional information:	. tot appneasie.
ADR Limited quantities (LQ)	11
Excepted quantities (EQ)	1L Code: E0
Excepted quantities (EQ)	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	(Contd. on page

Printing date: 13.03.2017 Version: 40 Revision: 13.03.2017

Trade name: Zettex High Wax Polish

(Contd. of page 7)

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:

Class	Share in %
Wasser NK	50-<75 25-<50

- · VOC-CH 28.50 %
- · VOC-EU 241.1 g/l
- · Danish MAL Code 5-3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

- · Department issuing SDS: Research & Development
- · Contact:
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure – Compressed gas

* Data compared to the previous version altered. *

GB