

SAFETY DATA SHEET

www.zettex.com

according to 1907/2006/EC, Article 31

Page 1/8

Revision: 14.03.2018

Printing date 14.03.2018

Version number 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: Primer Z-05
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Sealant
- 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Zettex Europe BV Plaza 20, 4782 SK Moerdijk The Netherlands +31(0)888-938839 info@zettex.nl www.zettex.nl

· Further information obtainable from:

Product safety department.

· 1.4 Emergency telephone number:

Zettex Europe BV 031 (0) 888 938 839 (Mon-Fri 09:00-17:00)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling: xylene

(Contd. on page 2)

Printing date 14.03.2018 Version number 2 Revision: 14.03.2018

Trade name: Primer Z-05

(Contd. of page 1)

· Hazard statements

H226 Flammable liquid and vapour.

H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information: TACTILE WARNING APPLICABLE FOR GENERAL PUBLIC

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Chemical characterisation: Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

	· Dangerous components:		
Γ	CAS: 1330-20-7	xylene	10-<30%
		♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4,	
	Reg.nr.: 01-2119488216-32-xxxx	H332; Skin Irrit. 2, H315	
Γ	EC number: 919-446-0	Naphtha (petroleum), hydrodesulfurized heavy	1-<5%
	Reg.nr.: 01-2119458049-33-xxxx	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic	
		2, H411; (1) STOT SE 3, H336	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact: Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 14.03.2018 Version number 2 Revision: 14.03.2018

Trade name: Primer Z-05

(Contd. of page 2)

 \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Pick up mechanically.

Ensure adequate ventilation.

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Use only in well ventilated areas.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- ·Storage
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Printing date 14.03.2018 Version number 2 Revision: 14.03.2018

Trade name: Primer Z-05

(Contd. of page 3)

· 8.1 Control parameters

·Ingre	Ingredients with limit values that require monitoring at the workplace:	
1330-	20-7 xylene	
WEL	Short-term value: 441 mg/m³, 100 ppm	

Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.35 mm

- · Penetration time of glove material >480min
- Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Colour: Various colours
Odour: Characteristic
Odour threshold: Not determined.

(Contd. on page 5)

Printing date 14.03.2018 Version number 2 Revision: 14.03.2018

Trade name: Primer Z-05

	(Contd. of page
pH-value:	Undetermined.
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. 2: Undetermined.
Flash point:	23 - 60 °C
· Flammability (solid, gas):	Not applicable.
Ignition temperature:	500 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits: Lower: Upper:	1.1 Vol % Undetermined. 7 Vol % Undetermined.
Vapour pressure:	Undetermined. Not determined.
Density at 20 °C: Relative density Vapour density Evaporation rate	0.93 g/cm³ Not determined. Not determined. Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: VOC (EC) VOC (EC) · 9.2 Other information	27.48 % 255.6 g/l No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

Printing date 14.03.2018 Version number 2 Revision: 14.03.2018

Trade name: Primer Z-05

(Contd. of page 5)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful in contact with skin or if inhaled.

· LD/LC50	LD/LC50 values relevant for classification:	
1330-20-7	xylene	
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	1,100 mg/kg (rabbit)
Inhalative	LC50/4 h	1.5 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European	waste catalogue
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

(Contd. on page 7)

Printing date 14.03.2018 Version number 2 Revision: 14.03.2018

Trade name: Primer Z-05

(Contd. of page 6)

• Uncleaned packaging:
• Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT PAINT
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
8	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Category	Warning: Flammable liquids. 30 F-E,S-E A
14.7 Transport in bulk according to Ann Marpol and the IBC Code	ex II of Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Tunnel restriction code	D/E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Printing date 14.03.2018 Version number 2 Revision: 14.03.2018

Trade name: Primer Z-05

(Contd. of page 7)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

- · **Department issuing SDS:** Product safety department.
- · Contact:

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.

-GB