



ZETTEX

STICK WITH US

TECHNICAL DATA SHEET

Eco Seal

Zettex Europe B.V.
Plaza 20, 4782 SK Moerdijk
The Netherlands
+31 (0)888-93 88 39
info@zettex.com
www.zettex.com

Product description

Zettex Eco Seal is a facade impregnating on water base. It leads to a perfect repellent application and it can be applied to both dry and damp surfaces. It can be applied on fresh masonry of at least 14 days old, as well.

Material

Ethanol

Benefits

- Repellent
- Paintable with synthetic paints.
- Application on most common materials.
- Dirt repellent.

Application

The Zettex Eco Seal is ready to use. It can be applied on almost every surface, for example on limestone, bricks, concrete, sandstone and plaster. Zettex Eco Seal is paintable with synthetic paints, it is dirt repellent it decreases lime retirement and frost damage on stone and joint works. It is alkali and acid proof as well.

Packaging

Barrel 1, 5 and 20 L.

Storage

24 months if stored in unopened, original packaging. Store at temperatures between 5°C and 25°C.

Propterties	Specifications
Basic raw material	30 to 35 g/m2
Consumption per M2	White
Isocyanate level	Up to -15°C
Product property 1	Façade Impregnation
Product property 2	Flooring and roofing felt cover
Product property 3	Don't apply when temperature is below 5°C
Product property 4	Ready to use