



**ZETTEX**  
STICK WITH US

## TECHNICAL DATA SHEET Spraybond X20 Canister

Zetex Europe B.V.  
Plaza 20, 4782 SK Moerdijk  
The Netherlands  
+31 (0)888-93 88 39  
[info@zettex.com](mailto:info@zettex.com)  
[www.zettex.com](http://www.zettex.com)

### Product description

Zetex Spraybond X20 Misty is an extremely quick-drying universal misting adhesive suitable for most materials in construction and industry.

### Material

SBR Rubber

### Advantages

- Extremely Fast drying
- Extremely powerful
- Mist spray
- For universal use
- Ready to use
- Barely penetrates porous materials
- DCM free

### Uses

For the adhesion and fastening of paper, wood, cork, decorative film, foil and textile materials, insulation, EPS, HPL, SKY and all kinds of leather or rubber.

### Application instructions

Dry the materials to be adhered and remove dust and grease. Then carefully spray the contact adhesive on both surfaces to be adhered. A distance between surface and spray gun of 30 cm is ideal. Preferably apply the adhesive in rows without overlapping. After 2-4 minutes adhere both surfaces to each other and firmly press or roll. With overlapping at least double the open time. With very porous surfaces carefully check whether there is sufficient contact between both adhesive layers. Apply an extra layer if this is required.

### Available form

Canister 18,9 kg

### Colour

Amber

### Safety recommendations

This technical information does not contain an MSDS (Material Safety Data Sheet). You must first fully read the MSDS before using this product.

Properties	Specifications
Processing temperature	+5 to +40 °C
Temperature resistance	-40 to + 100 °C
Consumption	70-80 gram/m <sup>2</sup>
Open time	3-4 min
Maximum yield	180 m <sup>2</sup>

Solids	45%
Color	Amber
Spray pattern	Mist
VOC	544 g/l