



STICK WITH US

TECHNICAL DATASHEET

Easycontact S90 Fleecebacked



Zettex Europe B.V.

Patrijsweg 1, 4791 RV Klundert

The Netherlands

+31 (0)888-93 88 39

info@zettex.com

www.zettex.com

Product description

Zettex Easycontact S90 Fleecebacked is a PU-based ready-to-use adhesive for fast and effective bonding of fleecebacked EPDM, PVC or TPO.

Material

Polyurethane.

Advantages

- Quick-drying.
- Very economical to use.
- Ready to use.
- Very powerful.
- Universally applicable.

Application areas

Suitable for PVC. Concrete, aerated concrete, mineralized bituminous roofing, aged bituminous roofing, laminated insulation material, wood, etc. Bonding on non-laminated insulation material is also possible, but it is important to apply the adhesive in a thin layer (approx. 160 g/m²) and to distribute the adhesive well (adhesive build-up should be avoided) and wait a few minutes before applying the roofing.

Utilization

Surfaces must be clean, dry and free of greasy substances. Moisture or condensation on surfaces must be avoided, as this greatly affects adhesion. Therefore, newly applied adhesive must be protected from drafts and should not be applied to substrates cooler than ambient air. The adhesive should only be processed in dry weather conditions at temperatures of at least + 5 °C.

Packaging

- Can 5 L, 10 L

Color

Transparent and yellow.

Safety recommendations

Always read the safety information before use.

Shelf life

12 months in unopened packaging. Store at temperatures between 5°C and 25°C.

Properties	Specification
Color	Transparent/yellow

Odor	Solvent
Viscosity	2,000 ± 400 mPa.s
Density	1,000 ± 10 kg/m ³
Solids content	81 ± 2 %
Consumption	100-150g/m ²