SAFETY DATA SHEET

www.zettex.com

according to 1907/2006/EC, Article 31

Version: 29

Page 1/9

Printing date: 24.04.2019 Revision: 24.04.2019 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: Multispray · Article number: · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Lubricant \cdot 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Zettex Europe BV Plaza 20, 4782 SK Moerdijk The Netherlands +31(0)888-938839 info@zettex.nl www.zettex.nl • 1.4 Emergency telephone number: +31(0)888-938839 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Aerosol 1 Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02 · Signal word Danger · Hazard-determining components of labelling: Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1% Solvent naphtha (petroleum), light arom. Benzene<0.1% Reaction mass of ethylbenzene and xylene isopropylbenzene · Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P260 Do not breathe mist/vapours/spray. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. (Contd. on page 2)

Printing date: 24.04.2019

Version: 29

Revision: 24.04.2019

Trade name: Multispray

	(Contd. of page 1)
P331 Do NOT induce vomiting.	
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	
· Additional information:	

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Active substance with propellant

· Dangerous components:		
CAS: 1174522-09-8	Hydrocarbons,C10-C13,n-alkanes,cyclic,<2%aromates, Benzene	25-<50%
EC number: 918-481-9	<0.1%	
Reg.nr.: 01-2119457273-39	Asp. Tox. 1, H304	
CAS: 106-97-8	butane (containing < 0.1% butadiene (203-450-8))	10-<25%
EINECS: 203-448-7	Flam. Gas 1, H220; Press. Gas (Comp.), H280	
Reg.nr.: 01-2119474691-32		
CAS: 74-98-6	propane	2.5-<10%
EINECS: 200-827-9	Flam. Gas 1, H220; Press. Gas (Comp.), H280	
Reg.nr.: 01-2119486944-21		
CAS: 75-28-5	isobutane (containing < 0,1 % butadiene (203-450-8))	1-<2.5%
EINECS: 200-857-2	Flam. Gas 1, H220; Press. Gas (Comp.), H280	
Reg.nr.: 01-2119485395-27		
· Additional information:	•	

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

· For safety reasons unsuitable extinguishing agents: Water with full jet

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date: 24.04.2019

Version: 29

Revision: 24.04.2019

(Contd. of page 2)

Trade name: Multispray

· 5.3 Advice for firefighters

· Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
• 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up:

- Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:
- Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility:
- Observe official regulations on storing packagings with pressurised containers.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:
- 1174522-09-8 Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%
- OEL Short-term value: 1200 mg/m³, 184 ppm

106-97-8 butane (containing < 0.1% butadiene (203-450-8))

- WEL Short-term value: 1810 mg/m³, 750 ppm
 - Long-term value: 1450 mg/m³, 600 ppm
 - Carc (if more than 0.1% of buta-1.3-diene)

(Contd. on page 4)

GB -

Printing date: 24.04.2019

Version: 29

Revision: 24.04.2019

(Contd. of page 3)

Trade name: Multispray

74-98-6 propane

WEL Long-term value: 1800 mg/m³

75-28-5 isobutane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 2400 mg/m³

Long-term value: 1900 mg/m³

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX/P2

Filter A/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2P2

Protection of hands:

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Safety glasses



Tightly sealed goggles

· Body protection: Use protective suit. (EN-13034/6)

(Contd. on page 5)

GB

Printing date: 24.04.2019

Version: 29

Revision: 24.04.2019

Trade name: Multispray

(Contd. of page 4)

0.1 Information on heads when it allowed a	L
9.1 Information on basic physical and c General Information	hemical properties
Appearance: Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	:-44.5 °C
Flash point:	-97 °C
Flammability (solid, gas):	Not applicable.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/
	vapour mixtures are possible.
	Not determined.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	10.9 Vol %
Vapour pressure at 20 °C:	3100 hPa
Density at 20 °C:	~0.727 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	75.8 %
Water:	0.1 %
Solids content:	4.2 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- \cdot 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)

GB

Version: 29

Printing date: 24.04.2019

Revision: 24.04.2019

(Contd. of page 5)

Trade name: Multispray

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

$^{\cdot}$ LD/LC50 values relevant for classification:

1174522-09-8 Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%

Oral	LD50	>5000 mg/kg (rat)
D	1 D50	5000 = 112

Dermal LD50 >5000 mg/kg (rabbit)

Inhalative LC50/4h >4951 mg/l (rat)

- · Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):
- \cdot Germ cell mutagenicity Based on available data, the classification criteria are not met.
- \cdot Carcinogenicity Based on available data, the classification criteria are not met.
- \cdot Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- \cdot STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard
- May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

×

· Aquatic toxicity:

1174522-09-8 Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%

EL0 (48h) 1000 mg/l (Daphnia magna)

EL0(72h) 1000 mg/l (Pseudokirchneriella subcapitata)

LL0(96h) 1000 mg/l (Oncorhynchus mykiss (96h))

- · 12.2 Persistence and degradability Easily biodegradable
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

GB

GB

Safety data sheet according to 1907/2006/EC, Article 31

Version: 29

Revision: 24.04.2019

Trade name: Multispray

*

Uncleaned packaging:
Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, ADN, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR, ADN IMDG	UN1950 AEROSOLS AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
ADN ADN/R Class:	2 5F
Class Label	2.1 2.1
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user Danger code (Kemler):	Warning: Gases.
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS:

(Contd. of page 6)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date: 24.04.2019

Version: 29

Revision: 24.04.2019

Trade name: Multispray

	(Contd. of page 7
· Transport/Additional information:	
· ADR	
 Limited quantities (LQ) 	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
 Limited quantities (LQ) 	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

Class Share in %

75-<100 NK

- · VOC-CH 75.74 %
- · VOC-EU ~550.7 g/l
- · Danish MAL Code 3-3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

· Department issuing SDS: Research & Development · Contact: · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark) LC50: Lethal concentration, 50 percent (Contd. on page 9)

Version: 29

Printing date: 24.04.2019

Revision: 24.04.2019

Trade name: Multispray

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1 Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas Asp. Tox. 1: Aspiration hazard – Category 1 (Contd. of page 8)

GB -