



**ZETTEX**

STICK WITH US

## TECHNICAL DATA SHEET

### PTFE Oil

**Zettex Europe B.V.**  
Plaza 20, 4782 SK Moerdijk  
The Netherlands  
+31 (0)888-93 88 39  
[info@zettex.com](mailto:info@zettex.com)  
[www.zettex.com](http://www.zettex.com)

#### Product description

Zettex PTFE Oil is a very high quality, universal PTFE-based lubricant that can be used in the most extreme conditions. Zettex PTFE Oil ensures perfect adhesion on almost any surface.

#### Material

Oil/PTFE

#### Product properties

- Ready to use
- Dissolves dirt and rust
- Excellent creeping properties
- Withstands very cold and very hot temperatures
- Lubricates up to 250°C
- Highly adhesive on all surfaces

#### Applications

For the long-lasting lubrication of all moving or hinged surfaces. For lubricating chains that are exposed to extreme conditions. As lubrication in lathes. As an universal lubrication on rusty surfaces.

#### Available forms

Aerosol 500 ml

#### Colour

Transparent/white

#### Safety recommendations

See safety information sheet.

Properties	Specification
Change in condition/boiling point	approx. 280°C
Density g/ml (20°C)	0,85gram/cm <sup>3</sup> DIN 51757
Viscosity mPas (20°C)	100cst
pH value undiluted (20°C)	12,5 DIN 19261
pH value (20°C)	11,6
Flash point (°C)	160 DIN 51755
Auto-ignition temperature (°C)	220 DIN 51794
Solubility in water (20°C)	Insoluble