

SAFETY DATA SHEET

According to 1907/2006 EEC Article 31

Page 1/13

Printing date: 13.03.2017 Version: 37 Revision: 13.03.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Zettex Zinc Spray
- · Article number:
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU21 Consumer uses: Private households / general public / consumers

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category

PROC11 Non industrial spraying

PROC7 Industrial spraying

- · Application of the substance / the mixture Spray varnish
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Zettex Europe BV

Plaza 20, 4782 SK Moerdijk

The Netherlands

+31(0)888-938839

info@zettex.nl

www.zettex.nl

• **1.4 Emergency telephone number:** +31(0)888-938839

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

*		
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
		(Contd. on page 2)

Contd. on page 2

Version: 37 Revision: 13.03.2017 Printing date: 13.03.2017

Trade name: Zettex Zinc Spray

(Contd. of page 1)

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS09

GHS02

GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

Acetone

xylene (mix)

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Causes skin irritation. H315 Causes serious eye irritation. H319

H336 May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure. H373

Very toxic to aquatic life with long lasting effects. H410

· Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

Do not pierce or burn, even after use. P251

Do not breathe spray. P260

P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves / eye protection. Avoid release to the environment. P273

Use only outdoors or in a well-ventilated area. P271

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Active substance with propellant

· Dangerous components:
CAS: 115-10-6

CAS: 115-10-6	dimethyl ether
EINECS: 204-065-8	Flam. Gas 1, H220; Press. Gas C, H280
Reg.nr.: 01-2119472128-37	

(Contd. on page 3)

25-<50%

Printing date: 13.03.2017 Version: 37 Revision: 13.03.2017

Trade name: Zettex Zinc Spray

	(0	Contd. of page 2)
CAS: 7440-66-6 EINECS: 231-175-3 Reg.nr.: 01-2119467174-37	zinc powder -zinc dust (stabilized) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	25-<50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-<25%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene (mix) Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons,C9,aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	2.5-<10%
CAS: 1314-13-2 EINECS: 215-222-5 Reg.nr.: 01-2119463881-32	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-<2.5%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	1.0-<2.5%

· Additional information:

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 4)

Printing date: 13.03.2017 Version: 37 Revision: 13.03.2017

Trade name: Zettex Zinc Spray

(Contd. of page 3)

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

 Ingredients v 	with limit val	nes that reani	re monitorin	g at the workplace:

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

67-64-1 Acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

1330-20-7 xylene (mix)

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

(Contd. on page 5)

Printing date: 13.03.2017 Version: 37 Revision: 13.03.2017

Trade name: Zettex Zinc Spray

DNELs				(Contd. of pa
	zinc powder -zinc d	ust (st	ahilized)	
Oral	-		50 mg/kg bw/day (Worker)	
Dermal			5000 mg/kg bw/day (Consumer)	
2 01111111	Er (EE Eeng win s)		5000 mg/kg bw/day (Worker)	
Inhalative	DNEL Long term-sy	stemic	2.5 mg/m3 (Consumer)	
			5 mg/m3 (Worker)	
67-64-1 A	cetone		<i>6</i> (** /	
Oral	DNEL Long term-sy	stemic	62 mg/kg bw/day (Consumer)	
Dermal	DNEL Long term-sy	stemic	62 mg/kg bw/day (Consumer)	
			186 mg/kg bw/day (Worker)	
Inhalative	DNEL Acute-local		2420 mg/m3 (Worker)	
	DNEL Long term-sy	stemic	200 mg/m3 (Consumer)	
			1210 mg/m3 (Worker)	
Hydrocar	bons,C9,aromatics			
Oral	DNEL Long term-sy	stemic	11 mg/kg bw/day (Consumer)	
Dermal	DNEL Long term-sy	stemic	11 mg/kg bw/day (Consumer)	
			25 mg/kg bw/day (Worker)	
Inhalative	DNEL Long term-sy	stemic	32 mg/m3 (Consumer)	
			100 mg/m3 (Worker)	
1314-13-2	zinc oxide			
Oral			0.83 mg/kg bw/day (Consumer)	
Dermal	DNEL Long term-sy	stemic	87 mg/kg bw/day (Consumer)	
			87 mg/kg bw/day (Worker)	
Inhalative	DNEL Long term-sy	stemic	2.5 mg/m3 (Consumer)	
			5 mg/m3 (Worker)	
67-63-0 pr				
Oral			26 mg/kg bw/day (Consumer)	
Dermal	DNEL Long term-sy	stemic	319 mg/kg bw/day (Consumer)	
T 1 1	DATE: I		888 mg/kg bw/day (Worker)	
Inhalative	DNEL Long term-sy	stemic	89 mg/m3 (Consumer)	
			500 mg/m3 (Worker)	
PNECs				
	zinc powder -zinc d			
			ng/l (Undefind)	
		_	6.1 ug/l (Undefind)	
		118 mg/kg (Undefind)		
			ng/kg (Undefind)	
PNEC Sewage Treatment Plant 5		_		
		36.5 n	ng/kg (Undefind)	
67-64-1 A		1.06	// / I C D	
PNEC Mar			ng/l (Undefind)	
			ng/kg (Undefind)	
PNEC Soil			ng/kg (Undefind)	
PNEC Marine water sediment 3.04		3.04 (Undefind)	

Printing date: 13.03.2017 Version: 37 Revision: 13.03.2017

Trade name: Zettex Zinc Spray

		(Contd. of page 5)		
1314-13	1314-13-2 zinc oxide			
PNEC F	Freshwater	20.6 ug/l (Undefind)		
PNEC N	Marine water	6.1 ug/l (Undefind)		
PNEC F	Freshwater sediment	117 mg/kg (Undefind)		
PNEC S	Soil	35.6 mg/kg (Undefind)		
PNEC S	Sewage Treatment Plant	52 ug/l (Undefind)		
PNEC N	Marine water sediment	56.5 mg/kg (Undefind)		
· Ingredi	ients with biological lin	nit values:		
1330-20	0-7 xylene (mix)			
BMGV	BMGV 650 mmol/mol creatinine Medium: urine			
	Sampling time: post sh	ift		
	Parameter: methyl hippuric acid			
· Additional Occupational Exposure Limit Values for possible hazards during processing:				
100-41-	-4 ethylbenzene			
	WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm			

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls

Sk 108-88-3 toluene

· Personal protective equipment:

WEL Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm

- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

· Protection of hands:

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.5 \text{ mm}$

· Penetration time of glove material

(Contd. on page 7)

Printing date: 13.03.2017 Version: 37 Revision: 13.03.2017

Trade name: Zettex Zinc Spray

(Contd. of page 6)

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Safety glasses



Tightly sealed goggles

· **Body protection:** Use protective suit. (EN-13034/6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Aerosol

Colour: According to product specification

Odour: Characteristic
Odour threshold: Not determined.

· **pH-value:** Not determined.

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** -24.9 °C

· Flash point: -42 °C

• Flammability (solid, gas): Not applicable.

• **Auto-ignition temperature:** Product is not selfigniting.

• **Explosive properties:** Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

Lower: 0.7 Vol % **Upper:** 18.6 Vol %

· Vapour pressure at 20 °C: 5200 hPa

• **Density at 20 °C:** 1.06 g/cm³

Relative densityVapour densityNot determined.Not determined.

• Evaporation rate Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

(Contd. on page 8)

Printing date: 13.03.2017 Version: 37 Revision: 13.03.2017

Trade name: Zettex Zinc Spray

	(Contd. of page ?
· Solvent content:	
Organic solvents:	64.3 %
Solids content:	5.1 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values rel	levant for classification:		
7440-66-6 zinc powder -zinc dust (stabilized)				
Oral LD50 >2000 mg/kg (rat)				
Inhalative	LC50/4h	>5.4 mg/l (rat)		
67-64-1 A	cetone			
Oral	LD50	5800 mg/kg (rat)		
Dermal	LD50	7800 mg/kg (rbt)		
Inhalative	LC50/4h	>20 mg/l (rat)		
1330-20-7	xylene (n	nix)		
Oral	LD50	4300 mg/kg (rat)		
Dermal LD50 2000 mg/kg (rbt)		2000 mg/kg (rbt)		
Hydrocarbons,C9,aromatics				
Oral LD50 3295 mg/kg (rat)		3295 mg/kg (rat)		
Dermal	LD50	>3160 mg/kg (rat)		
1314-13-2	zinc oxid	e		
Oral	LD50	>5000 mg/kg (rat)		
Dermal	LD50	>2000 mg/kg (rat)		
Inhalative	LC50/4h	>5700 mg/l (rat)		
	LC50	>5700 (4 hours) mg/L (rat)		
67-63-0 propan-2-ol				
Oral	LD50	5840 mg/kg (rat)		
Dermal	LD50	13900 mg/kg (rabbit)		
Inhalative	LC50/6h	25000 mg/m3 (rat)		
· Primary i	uuitaut afi	1 F4.		

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 9)

Printing date: 13.03.2017 Version: 37 Revision: 13.03.2017

Trade name: Zettex Zinc Spray

(Contd. of page 8)

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic toxic	•
7440-66-6 zin	c powder -zinc dust (stabilized)
EC50	354 ug/l (Daphnia Magna 48h)
NOEC/21d	178 ug/l (Crustaceeen-Palaemon elegans)
NOEC (72h)	9 mg/l (Ceratophyllum demersum)
	0.017 mg/l (Pseudokirchneriella subcapitata)
NOEC/72h	72.9 ug/l (Pseudokirchneriella subcapitata)
NOEC/4w	8.3 ug/l (Cyprinus carpio)
EC10/21d	59.2 ug/l (Daphnia magna)
EC10/72h	27.3 ug/l (algae)
EC50 (72h)	0.17 mg/l (Selenastrum capricornatum (72 h))
LC50/96h	0.41 mg/l (Oncorhynchus mykiss)
EC50/48h	1 mg/l (Daphnia magna)
EC50/96h	0.527 mg/l (algae)
LC50	238-269 ug/l (Pimephales promelas (96 h))
67-64-1 Aceto	ne
EC50	8800 mg/l (Daphnia magna)
	8300 (96h) mg/l (Fish)
1330-20-7 xyl	ene (mix)
LC50/96h	8.9-16.4 mg/l (Pimephales promelas)
EC50/48h	3.2-9.5 mg/l (Daphnia magna)
Hydrocarbon	s,C9,aromatics
NOELR (72h)	1 mg/l (Pseudokirchneriella subcapitata)
EL50(48h)	3.2 mg/l (Daphnia magna)
LL50 (96h)	9.2 mg/l (Oncorhynchus mykiss (96h))
1314-13-2 zin	c oxide
LC50	>320 mg/l (Lepomis macrochirus (96 h))
	1.1 mg/l (Oncorhynchus mykiss (96h))
	0.17 mg/l (Selenastrum capricornatum (72 h))
	2246 mg/l (Pimephales promelas (96 h))
NOEC (72h)	0.017 mg/l (Pseudokirchneriella subcapitata)
EC50 (72h)	0.17 mg/l (Selenastrum capricornatum (72 h))
EC50/48h	1 mg/l (Daphnia magna)
EC50	>1000 mg/l (Daphnia Magna 48h)

(Contd. on page 10)

Printing date: 13.03.2017 Version: 37 Revision: 13.03.2017

Trade name: Zettex Zinc Spray

(Contd. of page 9)

67-63-0 propar	67-63-0 propan-2-ol		
LOEC (8 days)	1000 mg/l (algae)		
LC50/96h	9640 mg/l (Pimephales promelas)		
LC50 (24h)	9714 mg/l (Daphnia magna)		

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Very toxic for fish
- · Additional ecological information:
- \cdot General notes:

Water danger class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, ADN, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR, ADN	UN1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
· IMDG · IATA	AEROSOLS (zinc powder -zinc dust (stabilized), Hydrocarbons,C9,aromatics), MARINE POLLUTANT AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- · ADR





(Contd. on page 11)

Printing date: 13.03.2017 Version: 37 Revision: 13.03.2017

Trade name: Zettex Zinc Spray

	(Contd. of page 1
ADN ADN/R Class:	2 5F
IMDG	
· Class · Label	2.1 2.1
IATA	
Class Label	2.1 2.1
14.4 Packing group	2.1
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Product contains environmentally hazardous substances: zinc powder -zinc dust (stabilized)
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler): EMS Number:	- F-D,S-U
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Anne Marpol and the IBC Code	x II of Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0
Transport category Tunnel restriction code	Not permitted as Excepted Quantity 2 D
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
	(Contd. on page

Printing date: 13.03.2017 Version: 37 Revision: 13.03.2017

Trade name: Zettex Zinc Spray

(Contd. of page 11)

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY

HAZARDOUS

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E1 Hazardous to the Aquatic Environment

P3a FLAMMABLE AEROSOLS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:

Class	Share in %
NK	50-<75

- · VOC-CH 64.30 %
- · VOC-EU 680.9 g/l
- · Danish MAL Code 5-3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS:

Produktsicherheit

Research & Development

· Contact:

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 13)

(Contd. of page 12)

Safety data sheet According to 1907/2006 EEC Article 31

Printing date: 13.03.2017 Version: 37 Revision: 13.03.2017

Trade name: Zettex Zinc Spray

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* * Data compared to the previous version altered. *