



ZETTEX

STICK WITH US

TECHNICAL DATA SHEET

Acrysol

Zettex Europe B.V.
Plaza 20, 4782 SK Moerdijk
The Netherlands
+31 (0)888-93 88 39
info@zettex.com
www.zettex.com

Product description

High quality, aromatics-free Acrysol for the removal of sticker remains from just about any surface. The Zettex Acrysol can also be used for degreasing materials or sealant edges that have to be painted. The product has high dissolving power and can also be used for removing silicones.

Advantages

- High dissolving power.
- Easy to apply.
- Available in different measures.

Application instructions

Remove the sticker from the surface. Pour plenty of the Acrysol (undiluted) on the Zettex Bonte or White Tricot cloth and clean the surface. First leave the Acrysol to evaporate from the surface before further treating.

Shelf life

Store at a temperature between +5 °C and +25 °C in the shade. The shelf life of Zettex Acrysol is 36 months if stored as recommended in unopened, original packaging.

Safety recommendations

See safety information sheet.

Properties	Specifications
Colour	Transparent
Density	0.78 kg/ltr
Flash point	<23°C
Temperature range	-20 till + 35 degrees
Odour	Strong solvent odour
Delivery forms	Can 1L, 5L, 25L en 210L
Material	Mixture of aliphatic hydrocarbons, alcohols, glycols and glycol ethers.