



**ZETTEX**  
STICK WITH US

## TECHNICAL DATA SHEET

### PU Fix

**Zettex Europe B.V.**  
Plaza 20, 4782 SK Moerdijk  
The Netherlands  
+31 (0)888-93 88 39  
[info@zettex.com](mailto:info@zettex.com)  
[www.zettex.com](http://www.zettex.com)

#### Product description

Zettex PU Fix is a single-part PU adhesive for gluing blocks and stones during building work. In comparison with mortar, PU Fix adheres the brickwork more easily and quickly. The use of the Zettex Foamgun is essential. Zettex PU Fix forms a strong adhesion within 30 minutes.

#### Material

Polyurethane

#### Advantages

- Ready to use
- Very fast
- Extremely powerful
- Easy to use
- Easy to dose.
- Multi-purpose.
- Nonflammable

#### Applications instructions

Used for the fast gluing of building block on non-supporting interior walls. Zettex PU Fix can also be used for the gluing of, for example, wooden paling in a garden. Zettex PU Fix can also be used outside for gluing different elements.

1. Hold the stone adhesive in an upward position, remove the cap from the adapter and screw the spray can on the Zettex Foamgun.
2. Make sure that the Foamgun is not pointing at other people while the spray can is being screwed on.
3. After fastening the Zettex PU Fix can it must be shaken at least twenty times before it can be used.
4. The surface must be moistened because PU Fix cures better and faster on surfaces moistened beforehand.
5. In cold weather conditions the PU Fix must be heated in a warm room or with warm water. The temperature may not exceed 30 degrees!
6. Join the stone surfaces immediately after the PU Fix has been applied.
7. Any non-cured foam can be removed with Zettex Foamcleaner. Hands can be cleaned with the Zettex Cleaning Wipes

#### Safety recommendations

This technical information does not contain an MSDS (Material Safety Data Sheet). You must first fully read the MSDS before using this product.

#### Packaging

- 500 ml HH Aerosol
- 750 ml NBS Aerosol

#### Shelf life

12 months in unopened packaging. Store at temperatures between 5°C and 25°C.

#### Certificates



Properties	Specifications
Touch dry time	8-15 min
Fully cured	24 hours
Fully cured (+5°C, 50 % RH)	72 hours
Fire class of hardened foam	B3
Flash point of hardened foam	600 °C
Temperature resistance of hardened foam	Long term: -40 to +90 degrees Short term: -40 to +110 degrees
Flammable	NO